



RoofTopGuard SA

Self-Adhered High Temp Underlayment

Classification:

Roof Covering and Roof Deck Construction – Underlayment
Shingles, Roof Tiles and Roof Coverings -07300

Product Name:

RoofTopGuard SA

Manufacturer:

Underlayment Specialties Plus, LLC
805 West 5th Street, Unit 10
Lansdale, PA 19446

www.uspunderlayment.com

Description:

RoofTopGuard SA is a synthetic based High-Temp Self-Adhered ice & water roof underlayment used in steep slope applications for use under: Metal, Tile, slate, asphalt based shingles, synthetic claddings and all others. RoofTopGuard SA polyethylene/polypropylene constructions results in a lightweight, extra-wide width roll that results in greater efficiency and coverage during installation. RoofTopGuard SA's unique adhesive allows very low installation temperatures (15 degrees or higher), while providing a larger service temperature (-20 degrees to 260 degrees). RoofTopGuard SA is constructed to be directional by having a 5" self-adhered topside selvage which provides a secure watertight lap adhesive bond.

Applications:

RoofTopGuard SA can be used under Tile installed over direct deck, battened or counter battened systems, Metal roofing, Slate, synthetic claddings and Composition shingles.

Installation:

RoofTopGuard SA High-Temp Self-Adhered membrane is installed by removing the split-release liner and applying the adhesive side against the roof deck with a 4" horizontal overlap and 12" vertical lap see installations instructions for details. The underlayment is laid horizontally (parallel) to the eave with the printed slip resistant side up and directional selvage edge on the top. A rosin slip-sheet is not required over RoofTopGuard SA with metal roof systems.